

SCHEDA TECNICA

M130 OIL P INDUSTRIAL VACUUM FOR OIL AND SWarf

ASPIRATORI INDUSTRIALI PER OLIO E TRUCIOLO

The M130 OIL P industrial vacuum cleaner has been engineered to vacuum and separate oil and metal chips from tanks, on machine tool tables and guides. Suction is generated by two motors working in parallel, ensuring excellent suction speed. The container of this vacuum cleaner is equipped with a metal basket to separate the solid part from the liquid part and a 150-micron nylon filter for more effective filtration. The electric floating level switch automatically stops suction when the maximum capacity of the container is reached (130 lt of extracted emulsified oil). An immersed pump allows simultaneous suction and discharge of the filtered liquid.



HIGHLIGHTS




VACUUM UNIT

Suction is provided by 2 by-pass motors. Each motor is operated by an independent switch that allows the operator to control suction performance. The suction motors are located in a sturdy metal casing, with an insulating sponge to maintain a low noise level.



FILTER UNIT

The collected liquid passes through a PPL filter with an efficiency of 150μ. Thanks to this, even the smallest solid particles can be separated, making the filtered liquid suitable for reuse. The filter can be washed and reused easily. A disposable TNT filter (100μ efficiency) is also available.



LIQUID DISCHARGE SYSTEM

An electric submerged pump is installed inside the container and allows the extracted and filtered liquids to be discharged quickly. Thanks to the non-return valve, it is possible to suction and discharge at the same time, without stopping the machine.

DATI TECNICI

MOTORE

Tipologia	by-pass
Voltaggio	230V
Massimo vuoto	250mBar
Massima portata d'aria	380m3/h
Livello di rumorosità	72dB(A)
Motori	2
Frequenza	50/60Hz
Potenza	3,5HP
Tempo di aspirazione	130/50

MACCHINA

Dimensioni	565 x 770mm
Altezza	1.415mm
Peso	53Kg
Capacità liquidi	130
Capacità solidi	40
Filtro olio	included
Tipologia di scarico	Submerged pump

OPZIONI

ALTRE OPZIONI



TX

Contentitore camera e struttura in acciaio INOX AISI 304

ACCESSORI



P12355

OLIO E TRUCIOLO KIT PRO Ø 50MM

Kit completo di accessori specifici per applicazione aspirazione olio e trucioli in diametro 50 mm



P12355

OLIO E TRUCIOLO KIT PRO Ø 50MM

Kit completo di accessori specifici per applicazione aspirazione olio e trucioli in diametro 50 mm