

SCHEDA TECNICA

INDUSTRIAL VACUUM UPF 220

ASPIRATORI INDUSTRIALI PER SFRIDI, CONFEZIONAMENTO E OEM

The **UPF 220** is a **compact industrial vacuum** for vacuuming on a machine. On this **vacuum cleaner** from the **food & pharma range**, a **side-channel turbine** is installed which ensures a **24/7 run** without the need for maintenance. The filter can be a **polyester bag** or **cartridge**, depending on the type of **material to be vacuumed**. The **metal inset**, fitted with a sturdy deflector, ensures the filter has a **long service life**. The **UPF 220 industrial vacuum** is equipped with a **20-liter stainless steel container** that facilitates the **collection of vacuumed material** and its subsequent disposal.



POTENZA
2,2 kW



CAPACITÀ
20 Lt

HIGHLIGHTS



SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The side channel blower is equipped with a safety valve to guarantee continued work in complete safety, without any maintenance. The blower is also equipped with a metal silencer to maintain a low noise level.



FILTERING ELEMENT

The filtration is guaranteed by a sturdy polyester filter.



INLET WITH DEFLECTOR

On the front part of the machine a metal nozzle acts as the point of entrance for the vacuumed material. The deflector inside it reduces the speed of the material, creating that way a cyclone effect inside the bin. This way a longer life for the filter is guaranteed and clogging probability far decreased



ELECTRIC PLUG

The robust plug provided as standard with the vacuum is certified IP 55 and is equipped with a practical phase inversion system which can be activated through a simple screwdriver turn.

DATI TECNICI

MOTORE

Tipologia	side channel blower
Voltaggio	400V
IP	55
Vuoto in continuo	210mBar
Massima portata d'aria	320m3/h
Livello di rumorosità	64dB(A)
Frequenza	50/60Hz
Potenza	3HP
Classe di isolamento	F

MACCHINA

Bocca aspirante	50Ø mm
Dimensioni	410 x 770mm
Altezza	550mm
Peso	42Kg