

#### SCHEDA TECNICA

# M100 OIL INDUSTRIAL VACUUM

### **ASPIRATORI INDUSTRIALI PER OLIO E TRUCIOLO**

The M100 OIL industrial vacuum is designed to vacuum and separate oil and swarf from the tanks, on the tables, and guides of tooling machines. Suction is generated by three motors that work in parallel and ensure an excellent suction speed. The container of this vacuum cleaner is equipped with a metal basket that is used to **separate** the **solid** part from the liquid part and a 150-micron nylon filter for more **effective filtration**. The floating level switch automatically stops the vacuum upon reaching maximum capacity in the container (100 lt of emulsified oil vacuumed). There is a level indicator on the outside of the container that indicates the amount of liquid inside the machine. Discharge takes place by gravity thanks to a 1" manual ball valve situated at the bottom of the container. The M100 OIL industrial vacuum container is mounted on wheels, and can be lifted with a forklift, to allow the operator to empty the vacuumed material easily; this way the liquid can be poured into a collection of sediment bins.







## HIGHLIGHTS



SUCTION UNIT

The vacuum is generated by 3 by-pass motors. Each motor is managed by an independent switch, permitting the operator to control the intake performance. The motors are located in a sturdy casing, with an insulating sponge to maintain a low noise level.



#### FILTERING ELEMENT

The collected liquid goes through a PPL filter with a 150  $\mu$  efficiency. Thanks to it it's possible to separate even the smallest solid particles, making the filtered liquid suitable for reuse. The filter can be washed and reused easily. An disposable TNT filter (efficiency 100  $\mu$ ) is also available.

### **DATI TECNICI**

×

MOTORE		FILTRO PRIMARIO		MACCHINA	
Tipologia	by-pass	Media	nylon	Bocca aspirante	50Ø mm
Voltaggio	230V			Dimensioni	700 x 450mm
Massimo vuoto	250mBar			Altezza	1.400mm
Massima portata d'aria	570m3/h			Peso	90Kg
Livello di rumorosità	72dB(A)			Capacità liquidi	100
Motori	3			Capacità solidi	50
Frequenza	50/60Hz			Filtro olio	incluso
Potenza	5,2HP			Efficienza filtrazione	150
Tempo di aspirazione	100/26			Tipologia di scarico	per gravità





OPZIONI

**BX** Contenitore in acciaio INOX AISI 304

# ACCESSORI



P12352 KIT OLIO E TRUCIOLO Ø 50MM. Kit base di accessori specifici per applicazione aspirazione olio e trucioli in diametro 50 mm



**ALTRE OPZIONI** 

P 12352 KIT OLIO E TRUCIOLO Ø 50MM. Kit base di accessori specifici per applicazione aspirazione olio e trucioli in diametro 50 mm

www.depureco.com | depureco@depureco.com