

SCHEDA TECNICA

PUMA 30 S INDUSTRIAL VACUUM

ASPIRATORI INDUSTRIALI TRIFASE AD ALTA POTENZA

The **Puma 30 S** is an industrial vacuum from Depureco's medium-large power three-phase range. It has a **high airflow high quality** Made in Italy double-stage **side channel blower** in parallel that ensures a maximum flow rate of **1100 m³/h**. The vacuum **breaker safety valve** is installed as standard. The **tangential intake** with the **sturdy cyclone** welded inside the filter chamber guarantee **excellent efficiency** even with the **finest dust**. The material, entering tangentially, meets the cyclone and due to the friction generated, loses speed and falls directly into the **container**. This system is extremely useful to **protect the filter** from the vacuumed material. The filter is in **Class M** high grammage polyester (certified by BIA Berufsgenossenschaftliches Institut für Arbeitssicherheit) with a **1µ filtration efficiency**. The filter can be customized to a specific application. For this **vacuum cleaner**, **anti-static filters** are available to prevent electrostatic charges, in **NOMEX** to withstand high temperatures (up to 250°C), **Teflon** coated to work with wet materials and with **PTFE** nanotechnology treatment to work with the most **difficult dust**. The **PUMA 30 S industrial vacuum** is equipped with a **manual filter cleaning system**. The filter can be shaken easily and effectively with the lever on the top of the vacuum. The vacuum can be configured with an automatic filter cleaning system on demand. Namely, there is a choice between **jet pulse cleaning**, **electro-pneumatic** piston filter shaker, or **electrical** filter shaker. Depureco's **PUMA 30 S** model is equipped with a handy and sturdy **175 L container**, fitted with a release system, which allows the operator to collect the **vacuumed material** and conveniently dispose of it. To facilitate handling the container, there are 4 castor wheels mounted on reinforced supports so that it can be handled easily even when it contains several kg of material. A kit is available on-demand for handling and unloading the container with a forklift.

**POTENZA**
20 kW**SUPERFICIE**
110.000 cm²**CAPACITÀ**
175 Lt

HIGHLIGHTS



SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The side channel blower is equipped with a safety valve to guarantee continued work in complete safety, without any maintenance. The blower is also equipped with a metal silencer to maintain a low noise level.



FILTERING ELEMENT

The filtration is guaranteed by an M class polyester filter. The star shape enables air to flow through the filter even when it is dirty. The fabric of the filter is classified as M Class (B1A | EN 60335-2-69). This means that all particles till 1 micron are stopped by the filter so as to protect the blower and the operator around the vacuum cleaner.



INLET

The tangential inlet is designed to ease the process of pushing the material down the bin. A sturdy metal cyclone welded inside the chamber slows the material's entry speed considerably down so that it falls directly inside the bin. This way, the filter is efficiently protected, minimizing clogging risk.



COLLECTION BIN

The material is collected inside a painted container equipped with a metal handle which enables the bin to be detached from the machine. Thanks to its 4 swiveling wheels, the bin can be easily moved and emptied. Each wheel is reinforced to guarantee maximum stability during handling.

DATI TECNICI

MOTORE

Tipologia	side channel blower
Voltaggio	400V
IP	55
Massimo vuoto	600mBar
Vuoto in continuo	460mBar
Massima portata d'aria	1.100m ³ /h
Valvola di sicurezza	included
Livello di rumorosità	78dB(A)
Frequenza	50/60Hz
Potenza	28HP
Classe di isolamento	F

FILTRO PRIMARIO

Tipologia	star filter
Classe EN 60335-2-69	M Class
Media	polyester
Pulizia filtro	electrical filter shaker

MACCHINA

Bocca aspirante	130Ø mm
Dimensioni	1.050 x 1.950mm
Altezza	2.300mm
Peso	620Kg
Ciclone conico	incluso

OPZIONI

MEDIA FILTRANTE DISPONIBILE


ANT M
 Filtro antistatico (Classe M EN 60335-2-69)



MTF
 Filtro teflonato (Classe M EN 60335-2-69)



NOMEX
 Filtro resistente 250° Celsius



PTFE
 Filtro PTFE (Classe M EN 60335-2-69)



HEPA 14
 Filtro assoluto (EN 1822)
 110.000 cm² superficie filtrante
 Classe H14 (EN 1822)
 Fibra di vetro

OPZIONI

SISTEMI DI PULIZIA FILTRO DISPONIBILI


COM
 Compressore a bordo
 Compressore montato su carenatura posteriore



PSC
 Scuotifiltro Pneumatico



SE
 Scuotifiltro Elettrico



SP
 Pulizia cartucce in controcorrente d'aria
 Filtro antistatico classe M (EN 60335-2-69)
 4 Filtri poliestere antistatici
 12 m² superficie filtrante

OPZIONI
ALTRE OPZIONI


BX
 Contenitore in acciaio INOX AISI 304



GX
 Camera e contenitore acciaio INOX AISI 304



FKL
 Supporto sollevamento per muletto



GFR
 Golfari



GRD
 Messa a terra



RC
 Controllo remoto 24 V ON/OFF

ACCESSORI



P12300/100

FLANGIA CONNESSIONE FLESSIBILE Ø 100MM

Flangia di accoppiamento su aspiratore industriale
DF per tubo flessibile diametro 100 mm



P12300/100

FLANGIA CONNESSIONE FLESSIBILE Ø 100MM

Flangia di accoppiamento su aspiratore industriale
DF per tubo flessibile diametro 100 mm



P12300/100

FLANGIA CONNESSIONE FLESSIBILE Ø 100MM

Flangia di accoppiamento su aspiratore industriale
DF per tubo flessibile diametro 100 mm



P12300/100

FLANGIA CONNESSIONE FLESSIBILE Ø 100MM

Flangia di accoppiamento su aspiratore industriale
DF per tubo flessibile diametro 100 mm