

## SCHEDA TECNICA

# INDUSTRIAL VACUUM

## PUMA FIX 25

### IMPIANTI DI ASPIRAZIONE CENTRALIZZATI

The **PUMA FIX 25** has a **high airflow** double-stage **side-channel blower** in parallel that ensures a **maximum flow rate** of **1380 m<sup>3</sup>/h**. The vacuum breaker safety valve is installed as standard. An **inverter** is installed in the **electrical panel** so that the **power of the vacuum cleaner** can be **modulated** according to the number of nozzles used in the system. The **tangential intake** together with the **sturdy cyclone** welded inside the filter chamber guarantee excellent efficiency even with the **finest dust**. The material, entering tangentially, meets the cyclone and due to the friction generated, loses speed and falls directly into the **container**. This system is extremely useful to protect the filter from the **vacuumed material**. The filter media consists of 4 **M Class** high grammage aluminized **polyester cartridges** (certified by BIA Berufsgenossenschaftliches Institut für Arbeitssicherheit) with a **1µ filtration efficiency**. An **automatic counter-blowing system** means that the **filters** always **stay clean**, even with the most **difficult dust**. Cleaning operations are **completely autonomous** and operator involvement is not required. Depureco's **PUMA FIX 25 industrial vacuum** is equipped with a handy and sturdy **175 L container**, fitted with a release system, which allows the operator to collect the **vacuumed material** and conveniently dispose of it. To facilitate handling the **container**, there are 4 castor wheels mounted on reinforced supports so that it can be **handled easily** even when it contains several kg of material. A kit is available on-demand for handling and unloading the container with a forklift.

**POTENZA**  
18,5 kW**SUPERFICIE**  
120.000 cm<sup>2</sup>**CAPACITÀ**  
175 Lt

## HIGHLIGHTS



### SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The side channel blower is equipped with a safety valve to guarantee continued work in complete safety, without any maintenance. The blower is also equipped with a metal silencer to maintain a low noise level.



### FILTERING ELEMENT

The filtration is guaranteed by a filter cartridge in antistatic polyester. The cartridge has been developed in order to maintain a large surface in a compact space enabling the air to flow through it even when the cartridge is dirty. The cartridge is classified as M Class (BIA | EN 60335-2-69). This means that all particles till 1 micron are stopped by the filter so as to protect the blower and the operator around the vacuum cleaner.



### INLET

The tangential inlet is designed to ease the process of pushing the material down the bin. A sturdy metal cyclone welded inside the chamber slows the material's entry speed considerably down so that it falls directly inside the bin. This way, the filter is efficiently protected, minimising clogging risk.



### COLLECTION BIN

The material is collected inside a painted container equipped with a metal handle which enables the bin to be detached from the machine. Thanks to its 4 swiveling wheels, the bin can be easily moved and emptied. Each wheel is reinforced to guarantee maximum stability during handling.

## DATI TECNICI

### MOTORE

Voltaggio	400V
Massimo vuoto	420mBar
Vuoto in continuo	330mBar
Massima portata d'aria	1.350m3/h
Livello di rumorosità	74dB(A)
Frequenza	50/60Hz
Potenza	25HP

### FILTRO PRIMARIO

Tipologia	star filter
Classe EN 60335-2-69	M Class
Media	polyester
Pulizia filtro	PSC

### MACCHINA

Inverter	opzionale
----------	-----------

**OPZIONI**

**SISTEMI DI PULIZIA FILTRO DISPONIBILI**

**COM**

Compressore a bordo  
 Compressore montato su carenatura posteriore


**SP**

Pulizia cartucce in controcorrente d'aria  
 Filtro antistatico classe M (EN 60335-2-69)  
 4 Filtri poliestere antistatici  
 12 m² superficie filtrante

**OPZIONI**
**ALTRE OPZIONI**

**BX**

Contentore in acciaio INOX AISI 304


**GX**

Camera e contenitore acciaio INOX AISI 304


**FKL**

Supporto sollevamento per muletto


**GFR**

Golfari

**ACCESSORI**

**P00285**

**TERMINALE IN ACCIAIO Ø 100/100MM**

Riduzione per innesto rapido aspiratore in acciaio zincato diametro 100/100 mm