

SINGLE-PHASE WET&DRY INDUSTRIAL VACUUM CLEANERS

XM 20 JC COMPACT INDUSTRIAL VACUUM CLEANER



Watch the video!





POWER 2,6 kW - 3,5 HP



APPLICATION
Fine, dry and clogging powders



CAPACITY 20 Lt



FEATURES

- High filtration capacity and efficiency
- Compact and handy

- Sturdy painted steel construction
- Multiple construction options available

HIGHLIGHTS




SUCTION UNIT

Suction is provided by 2 by-pass motors controlled by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



FILTER UNIT

Filtration is ensured by a Class M polyester cartridge filter (filtration efficiency 1 micron) with a high filtering surface area, which guarantees air passage even with a dirty filter.



JET CLEAN FILTER CLEANING SYSTEM

Equipped with JetClean® filter cleaning system. Due to the different pressure between the outside and inside of the vacuum cleaner, the system generates a flow of air through the cartridge that detaches dust from the surface of the filter, keeping the filter efficient while working and without stopping suction.

.....



COLLECTION UNIT

The material is collected inside a coated bin complete with a handle that allows its release. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease, and the collected material can then be disposed of.

TECHNICAL DATA

MUTUR	
Typologies	By-pass
Power	2,6 kW - 3,5 HP
Frequency	50/60 Hz
Voltage	230 V
Vacuum in continuous run	250 mBar
Maximum air flow	380 m3/h
Noise level	72 dB(A)

MACHINE	
Suction inlet	50 Ø mm
Collection system	Steel container
Capacity	20 Lt
Dimensions	516 x 545 mm
Height	994 mm
Weight	38 Kg

FILTRATION

Primary filter type	Cartridge
Filter surface	16000 cm2
EN 60335-2-69 filtration class	М
Media	Polyester
Filter Cleaning System	Jet Clean
JetClean Guillotine	Included



FEATURES



FILTER CLOGGING INDICATOR

Filter clogged or need to be replaced indicator light



POWER SUPPLY CABLE



SHUKO TYPE PLUG



DEFLECTOR

Internal deflector to protect the filter



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



SD

Sliding damper



JC

Jet Clean



OPTIONS

AVAILABLE FILTER MEDIA



HEPA 13

Absolute filter (EN 1822) 35.000 cm² filter surface H13 Class Filter (EN 1822) Glass fiber



HEPA 14

Absolute filter (EN 1822) 22.000 cm² filter surface H14 Class Filter (EN 1822) Glass fiber

STRUCTURE AND OPTIONS



60H7

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with the vacuum



RC SCHUKO

Remote control by power tool (MAX 2000 W)



GRD

Grounding



BX

Stainless steel bin AISI 304



ACCESSORIES



P13638 Starter Kit Ø 40mm

Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P13640

DRY KIT Ø 40MM

Kit containing specific accessories for 40 mm diameter dust and solids vacuuming