

SINGLE-PHASE WET&DRY INDUSTRIAL VACUUM CLEANERS

MINIBULL BAGLESS INDUSTRIAL VACUUM CLEANER



Watch the video!





POWER 2,6 kW - 3,5 HP



APPLICATION
Powders, solids and shavings



CAPACITY 45 Lt



FEATURES

- Ideal for professional and industrial applications
- Durable, high-strength steel construction
- Powerful, versatile and compact
- Multiple construction options available

HIGHLIGHTS



SUCTION UNIT

Suction is provided by 2 by-pass motors controlled by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



FILTER UNIT

Filtration is provided by a polyester star filter in class M (filtration efficiency 1 micron) with a high filtering surface area, which guarantees the passage of air even with a dirty filter.



FILTER CLEANING SYSTEM

An ergonomic manual filter shaker allows the filter to be cleaned easily and quickly, removing dust and debris from the surface of the filter.



COLLECTION UNIT

The material is collected inside a coated bin complete with a handle that allows it to be released. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease and the collected material can then be disposed of.

TECHNICAL DATA

MUTUR	
Typologies	By-pass
Power	2,6 kW - 3,5 HP
Frequency	50/60 Hz
Voltage	230 V
Vacuum in continuous run	250 mBar
Maximum air flow	380 m3/h
Noise level	72 dB(A)
·	

MACHINE	
Suction inlet	70 Ø mm
Collection system	Steel container
Capacity	45 Lt
Dimensions	550 x 620 mm
Height	1240 mm
Weight	45 Kg

FILTRATION

Primary filter type	Star
Filter surface	15000 cm2
EN 60335-2-69 filtration class	М
Media	Polyester
Filter Cleaning System	Manual
JetClean Guillotine	Included



FEATURES



FILTER CLOGGING INDICATOR

Filter clogged or need to be replaced indicator light



POWER SUPPLY CABLE



SHUKO TYPE PLUG



DEFLECTOR

Internal deflector to protect the filter



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14 Absolute filter (EN 1822) 22.000 cm² filter surface H14 Class Filter (EN 1822) Glass fiber



PTFE ANT Antistatlc PTFE filter (M class EN 60335-2-69)



PTFE
PTFE Filter (M class EN 60335-2-69)



NOMEX 250° Celsius resistant filter



MTF Teflon filter (M class EN 60335-2-69)



ANT MAntistatic filter (M class EN 60335-2-69)



STRUCTURE AND OPTIONS

60[®]HZ

60HZ

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with



RC SCHUKO

Remote control by power tool (MAX 2000 W)



GRD

Grounding



GX

Stainless steel bin and chamber AISI 304



ВХ

Stainless steel bin AISI 304



AB

Accessories basket



KDP

Differential pressure KIT for bag



FLT

Floater device

ACCESSORIES



P12350

STARTER KIT Ø 50MM

Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P11887

WET & DRY KIT Ø 50MM

Kit containing specific accessories for 50 mm diameter solids and liquids vacuuming