

## SINGLE-PHASE WET&DRY INDUSTRIAL VACUUM CLEANERS

# XM 35 JC CYCLONIC INDUSTRIAL VACUUM CLEANER



Watch the video!





POWER 2,6 kW - 3,5 HP



APPLICATION
Fine, dry and clogging powders



CAPACITY 45 Lt



## **FEATURES**

- · Ideal for fine dust
- Large surface area M-class filter

- Powerful, versatile and compact
- Multiple construction options available

## HIGHLIGHTS




## **SUCTION UNIT**

Suction is provided by 2 by-pass motors controlled by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



## **FILTER UNIT**

Filtration is ensured by a Class M polyester cartridge filter (filtration efficiency 1 micron) with a high filtering surface area, which guarantees air passage even with a dirty filter.



## JET CLEAN FILTER CLEANING SYSTEM

Equipped with JetClean® filter cleaning system. Due to the different pressure between the outside and inside of the vacuum cleaner, the system generates a flow of air through the cartridge that detaches dust from the surface of the filter, keeping the filter efficient while working and without stopping suction.



#### **COLLECTION UNIT**

The material is collected inside a coated bin complete with a handle that allows it to be released. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease and the collected material can then be disposed of.

# **TECHNICAL DATA**

MUTUK	
Typologies	By-pass
Power	2,6 kW - 3,5 HP
Frequency	50/60 Hz
Voltage	230 V
Vacuum in continuous run	250 mBar
Maximum air flow	380 m3/h
Noise level	72 dB(A)

MACHINE	
Suction inlet	50 Ø mm
Collection system	Steel container
Capacity	45 Lt
Dimensions	585 x 545 mm
Height	1285 mm
Weight	45 Kg

#### **FILTRATION**

Primary filter type	Cartridge
Filter surface	35000 cm2
EN 60335-2-69 filtration class	М
Media	PTFE coated polyester
Filter Cleaning System	Jet Clean
JetClean Guillotine	Included



## **FEATURES**



FILTER CLOGGING INDICATOR

Filter clogged or need to be replaced indicator light



**POWER SUPPLY CABLE** 



SHUKO TYPE PLUG



WHEELS

Non-marking pivoting wheels



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



STEEL CONSTRUCTION

Rugged industrial coated steel construction



#### CYCLONIC EFFECT

Tangential inlet and cyclone installed



**PUSH HANDLE** 



## **OPTIONS**

## **AVAILABLE FILTER MEDIA**



HEPA 13 Absolute filter (EN 1822) 35.000 cm² filter surface H13 Class Filter (EN 1822) Glass filter



HEPA 14 Absolute filter (EN 1822) 22.000 cm² filter surface H14 Class Filter (EN 1822) Glass fiber



PTFE ANT Antistatlc PTFE filter (M class EN 60335-2-69)



PTFE
PTFE Filter (M class EN 60335-2-69)



**NOMEX** 250° Celsius resistant filter



MTF
Teflon filter (M class EN 60335-2-69)



ANT M
Antistatic filter (M class EN 60335-2-69)

# STRUCTURE AND OPTIONS

60<sup>®</sup>

**60HZ** Available in 60Hz version



**3 YEARS WARRANTY**Purchasing the replacement filter along with the vacuum



RC SCHUKO Remote control by power tool (MAX 2000 W)



LP
Endless Bag continuous roll collection system



**KDP**Differential pressure KIT for bag



**GRD**Grounding



**BX** Stainless steel bin AISI 304



**AB** Accessories basket



# **ACCESSORIES**



#### P12350 Starter Kit Ø 50MM

Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



#### P11887

### WET & DRY KIT Ø 50MM

Kit containing specific accessories for 50 mm diameter solids and liquids vacuuming