

SINGLE-PHASE WET&DRY INDUSTRIAL VACUUM CLEANERS

M100

POWERFUL INDUSTRIAL VACUUM



Watch the video!



POWER
3,9 kW - 5,2 HP



APPLICATION
Powders, solids and
shavings




CAPACITY
100Lt

FEATURES


- Powerful and reliable steel industrial vacuum cleaner
- Specific filters for materials with different characteristics
- Ability to vacuum dust, solids and liquids
- Multiple construction options available

HIGHLIGHTS



SUCTION UNIT

Suction is provided by 3 by-pass motors operated by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



FILTER UNIT

Filtration is provided by a polyester star filter in class M (filtration efficiency 1 micron) with a high filtering surface area, which guarantees the passage of air even with a dirty filter.



FILTER CLEANING SYSTEM

An ergonomic manual filter shaker allows the filter to be cleaned easily and quickly, removing dust and debris from the surface of the filter.



COLLECTION UNIT

The material is collected inside a coated container complete with a handle that allows its release. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease, and the collected material can then be disposed of.

TECHNICAL DATA

MOTOR

Typologies	By-pass
Power	3,9 kW - 5,2 HP
Frequency	50/60 Hz
Voltage	230 V
Vacuum in continuous run	250 mBar
Maximum air flow	570 m3/h
Noise level	72 dB(A)

MACHINE

Suction inlet	70 Ø mm
Collection system	Steel container
Capacity	100 Lt
Dimensions	660 x 800 mm
Height	1515 mm
Weight	80 Kg

FILTRATION


Primary filter type	Star
Filter surface	24000 cm2
EN 60335-2-69 filtration class	M
Media	Polyester
Filter Cleaning System	Manual

FEATURES



VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement



DEFLECTOR

Internal deflector to protect the filter



POWER SUPPLY CABLE



SHUKO TYPE PLUG



PUSH HANDLE



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction

OPTIONS

AVAILABLE FILTER CLEANING SYSTEMS



SP

Automatic reverse jet cleaning system
Antistatic M class filter (EN 60335-2-69), 3
Polyester filter cartridges, 9 m² filter surface



COM

Compressor on board
Compressor fitted on the back cover

AVAILABLE FILTER MEDIA



PTFE ANT

Antistatic PTFE filter (M class EN 60335-2-69)



PTFE

PTFE Filter (M class EN 60335-2-69)



NOMEX

250° Celsius resistant filter



MTF

Teflon filter (M class EN 60335-2-69)



ANT M

Antistatic filter (M class EN 60335-2-69)



HEPA 14

Absolute filter (EN 1822)
28.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber

STRUCTURE AND OPTIONS

60^{Hz}

60HZ

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with the vacuum



RC SCHUKO

Remote control by power tool (MAX 2000 W)



CYCLONIC EFFECT

Tangential inlet and cyclone installed
Tangential inlet + cyclone



LP

Endless Bag continuous roll collection system



KDP

Differential pressure KIT for bag



GRD

Grounding



FLT

Floater device



BX

Stainless steel bin AISI 304




GX

Stainless steel bin and chamber AISI 304



TX

Stainless steel bin, chamber and frame AISI 304



AB

Accessories basket



CONTAINER EMPTYING KIT

System for easy container emptying using forklift lifting.

ACCESSORIES



P13970
ARTICULATED SUCTION ARM D70
Flexible PVC suction arm, retrofittable on existing models - 1.2 mt length - d70



P13640
DRY KIT Ø 40MM
Kit containing specific accessories for 40 mm diameter dust and solids vacuuming



P12348
DRY KIT Ø 50MM
Kit containing specific accessories for 50 mm diameter dust and solids vacuuming



P13638
STARTER KIT Ø 40MM
Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P12350
STARTER KIT Ø 50MM
Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13639
WET & DRY KIT Ø 40MM
Kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P11887
WET & DRY KIT Ø 50MM
Kit containing specific accessories for 50 mm diameter solids and liquids vacuuming