

SINGLE-PHASE WET&DRY INDUSTRIAL VACUUM CLEANERS

M65 JC

INDUSTRIAL VACUUM



Watch the video!



POWER
3,9 kW - 5,2 HP



APPLICATION
Fine, dry and clogging
powders




CAPACITY
65Lt

FEATURES

- Powerful and reliable industrial steel vacuum cleaner
- High filtration efficiency
- Ideal for vacuuming up fine dust
- Multiple construction options available

HIGHLIGHTS




SUCTION UNIT

Suction is provided by 3 by-pass motors operated by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



FILTER UNIT

Filtration is ensured by a Class M polyester cartridge filter (filtration efficiency 1 micron) with a high filtering surface area, which guarantees air passage even with a dirty filter.



JET CLEAN FILTER CLEANING SYSTEM

Equipped with JetClean® filter cleaning system. Due to the different pressure between the outside and inside of the vacuum cleaner, the system generates a flow of air through the cartridge that detaches dust from the surface of the filter, keeping the filter efficient while working and without stopping suction.



COLLECTION UNIT

The material is collected inside a coated container complete with a handle that allows its release. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease, and the collected material can then be disposed of.

TECHNICAL DATA

MOTOR

Typologies	By-pass
Power	3,9 kW - 5,2 HP
Frequency	50/60 Hz
Voltage	230 V
Vacuum in continuous run	250 mBar
Maximum air flow	570 m3/h
Noise level	72 dB(A)


MACHINE

Suction inlet	50 Ø mm
Collection system	Steel container
Capacity	65 Lt
Dimensions	660 x 800 mm
Height	1300 mm
Weight	80 Kg

FILTRATION

Primary filter type	Cartridge
Filter surface	35000 cm2
EN 60335-2-69 filtration class	M
Media	PTFE coated polyester
Filter Cleaning System	Jet Clean
JetClean Guillotine	Included

FEATURES



DEFLECTOR
Internal deflector to protect the filter



PUSH HANDLE



VACUUM GAUGE
Vacuum gauge for indication of filter clogged or in need of replacement



SHUKO TYPE PLUG



POWER SUPPLY CABLE



WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELS
Non-marking pivoting wheels



STEEL CONSTRUCTION
Rugged industrial coated steel construction



SD
Sliding damper



JC
Jet Clean

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 13
Absolute filter (EN 1822)
35.000 cm² filter surface
H13 Class Filter (EN 1822)
Glass fiber



HEPA 14
Absolute filter (EN 1822)
22.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber

STRUCTURE AND OPTIONS



60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



RC SCHUKO
Remote control by power tool (MAX 2000 W)



LP
Endless Bag continuous roll collection system



KDP
Differential pressure KIT for bag




GRD
Grounding



FLT
Floater device



BX
Stainless steel bin AISI 304



AB
Accessories basket



CONTAINER EMPTYING KIT
System for easy container emptying using forklift lifting.

ACCESSORIES


P13638
STARTER KIT Ø 40MM
 Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P12350
STARTER KIT Ø 50MM
 Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13640
DRY KIT Ø 40MM
 Kit containing specific accessories for 40 mm diameter dust and solids vacuuming



P12348
DRY KIT Ø 50MM
 Kit containing specific accessories for 50 mm diameter dust and solids vacuuming



P13639
WET & DRY KIT Ø 40MM
 Kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P11887
WET & DRY KIT Ø 50MM
 Kit containing specific accessories for 50 mm diameter solids and liquids vacuuming