

HEAVY DUTY THREE-PHASE INDUSTRIAL VACUUM CLEANERS

TX750 P JC LP TAN INDUSTRIAL VACUUM CLEANER WITH ADJUSTABLE BAG COLLECTION





POWER 7.5 kW - 10 HP



APPLICATION

Toxic or hazardous dusts




COLLECTION SYSTEM
Endless bag



FEATURES

- Industrial steel vacuum cleaner, powerful and reliable
- Suitable for continuous work, 24 hours a day, 7 days a week
- Cyclonic effect and high surface area M-class filter
- Endless Bag collection to avoid contact with dust

HIGHLIGHTS




SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve to ensure continuous, maintenance-free work. A metal silencer is included as standard in the turbine to ensure a low noise level.



FILTER UNIT

Filtration is ensured by a Class M polyester cartridge filter (filtration efficiency 1 micron) with a high filtering surface area, which guarantees air passage even with a dirty filter.



JET CLEAN FILTER CLEANING SYSTEM

Equipped with JetClean® filter cleaning system. Due to the different pressure between the outside and inside of the vacuum cleaner, the system generates a flow of air through the cartridge that detaches dust from the surface of the filter, keeping the filter efficient while working and without stopping suction.



COLLECTION UNIT

The material is collected inside a sturdy 20-meter-long adjustable roll plastic bag. Once the bag is filled, simply seal and remove it, with no contact between operator and material.

TECHNICAL DATA

MOTOR	
Typologies	Side channel blower
Power	7,5 kW - 10 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	260 mBar
Maximum air flow	730 m3/h
Noise level	79 dB(A)

MACHINE

Suction inlet	70 Ø mm
Collection system	Endless Bag
Dimensions	650 x 1100 mm
Height	1750 mm
Weight	200 Kg

FILTRATION

Primary filter type	Cartridge
Filter surface	35000 cm2
EN 60335-2-69 filtration class	М
Media	PTFE coated polyester
Filter Cleaning System	Jet Clean
JetClean Guillotine	Included



FEATURES



STEEL CONSTRUCTION
Rugged industrial coated steel construction



WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELSNon-marking pivoting wheels



LPEndless Bag continuous roll collection system



CYCLONIC EFFECTTangential inlet and cyclone installed



SD Sliding damper



JC Jet Clean



PRV Pressure relief valve installed



COM Compressor on board



VACUUM GAUGE
Vacuum gauge for indication of filter clogged or in need of replacement



OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14

Absolute filter (EN 1822) 28.000 cm² filter surface H14 Class Filter (EN 1822) Glass fiber

STRUCTURE AND OPTIONS



60HZ

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with the vacuum



ACCESSORIES



P13638 Starter Kit Ø 40mm

Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P12350 Starter kit Ø 50mm

Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13640

DRY KIT Ø 40MM

Kit containing specific accessories for 40 mm diameter dust and solids vacuuming



P12348

DRY KIT Ø 50MM

Kit containing specific accessories for 50 mm diameter dust and solids vacuuming



P11717

"Y" REDUCER BRANCH Ø 70/50/50MM

Galvanised steel "Y" reducer 70/50/50 mm