

DUST EXTRACTORS FOR TOXIC AND HAZARDOUS DUSTS

TX550 P SP LP TAN

INDUSTRIAL VACUUM CLEANER WITH CYCLONIC EFFECT AND AUTOMATIC FILTER CLEANING



POWER
5,5 kW - 7,5 HP



APPLICATION
Toxic or hazardous dusts



COLLECTION SYSTEM
Endless bag

FEATURES

- Powerful and reliable steel industrial vacuum cleaner
- Suitable for continuous work, 24 hours a day, 7 days a week
- Cyclonic effect and high surface area M-class filter
- Endless Bag collection to avoid contact with dust

HIGHLIGHTS




SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve to ensure continuous, maintenance-free work. A metal silencer is included as standard in the turbine to ensure a low noise level.



FILTER UNIT

The tangential inlet facilitates the deposition of the sucked material in the container due to the cyclonic effect. Filtration is ensured by a polyester cartridge filter in class M (filtration efficiency 1 micron) with a high filtering surface area, which guarantees the passage of air even with a dirty filter.



SP FILTER CLEANING SYSTEM

Automatic filter cleaning system in reverse flow of air at 6 bar (compressed air not supplied as standard). Each filter is cleaned at regular, adjustable intervals alternately without interrupting suction. Ideal for fine and difficult dust.



COLLECTION UNIT

The material is collected inside a sturdy 20-meter-long adjustable roll plastic bag. Once the bag is filled, simply seal and remove it, with no contact between operator and material.

TECHNICAL DATA

MOTOR

Typologies	Side channel blower
Power	5,5 kW - 7,5 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	260 mBar
Maximum air flow	530 m3/h
Noise level	74 dB(A)

MACHINE

Suction inlet	80 Ø mm
Collection system	Endless Bag
Dimensions	650 X 1100 mm
Height	1750 mm
Weight	165 Kg

FILTRATION

Primary filter type	3x Cartridges
Filter surface	90000 cm2
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Filter Cleaning System	Automatic SP

FEATURES



VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement



SHUKO TYPE PLUG



POWER SUPPLY CABLE



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



CYCLONIC EFFECT

Tangential inlet and cyclone installed



SP

Automatic reverse jet cleaning system



COM

Compressor on board

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14

Absolute filter (EN 1822)
 28.000 cm² filter surface
 H14 Class Filter (EN 1822)
 Glass fiber

STRUCTURE AND OPTIONS

60^{Hz} 

60HZ

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with the vacuum

ACCESSORIES



P13638

STARTER KIT Ø 40MM

Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P12350

STARTER KIT Ø 50MM

Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13640

DRY KIT Ø 40MM

Kit containing specific accessories for 40 mm diameter dust and solids vacuuming



P12348

DRY KIT Ø 50MM

Kit containing specific accessories for 50 mm diameter dust and solids vacuuming