

DUST COLLECTORS

DF 22 DUST COLLECTOR



Watch the video!





POWER 2,2 kW - 3 HP



APPLICATION

Volatile and suspended powders



CAPACITY 65 Lt



FEATURES

- Very high air flow rates for suspended dust
- High filtration capacity and efficiency

- Sturdy painted steel construction
- Suction arm available (also Atex certified)

HIGHLIGHTS



SUCTION UNIT

The suction is generated by a specially designed electric fan to ensure the best air flow rate while maintaining a good level of water lift.



FILTER UNIT

The material is diverted by a deflector protecting the main filter. Filtration is ensured by a class M polyester star filter (filtration efficiency 1 micron) with high filtering surface area, which guarantees air passage even with the dirty filter.



FILTER CLEANING SYSTEM

An ergonomic manual filter shaker allows the filter to be cleaned easily and quickly, removing dust and debris from the surface of the filter.



COLLECTION UNIT

The material is collected inside a coated container complete with a handle that allows its release. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease, and the collected material can then be disposed of.

TECHNICAL DATA

MOTOR	
Typologies	Electric Fan
Power	2,2 kW - 3 HP
Frequency	50/60 Hz
Voltage	400 V
Maximum vacuum mmH20	350 350 350 mmH2O
Static depression level	340 320 280 mmH2O
Maximum air flow	800 1000 1400 m3/h
Insulation class	55 F IP
Noise level	73 dB(A)
·	·

MACHINE	
Suction inlet	100 120 150 Ø mm
Collection system	Steel container
Capacity	65 Lt
Dimensions	660 x 800 mm
Height	1630 mm
Weight	120 Kg

FILTRATION

Primary filter type	Star
Filter surface	24000 cm2
EN 60335-2-69 filtration class	М
Media	Polyester
Filter Cleaning System	Manual



FEATURES





PLUG 4-pole industrial plug



POWER SUPPLY CABLE

WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELSNon-marking pivoting wheels



STEEL CONSTRUCTIONRugged industrial coated steel construction

OPTIONS

AVAILABLE FILTER CLEANING SYSTEMS



SPAutomatic reverse jet cleaning system
Antistatic M class filter (EN 60335-2-69), 3
Polyester filter cartridges, 9 m² filter surface



AVAILABLE FILTER MEDIA



HEPA 13 Absolute filter (EN 1822) 35.000 cm² filter surface H13 Class Filter (EN 1822) Glass fiber



PTFE ANT Antistatlc PTFE filter (M class EN 60335-2-69)



PTFE
PTFE Filter (M class EN 60335-2-69)



NOMEX 250° Celsius resistant filter



BFL M class filter 38.000 cm ²



ANT M Antistatic filter (M class EN 60335-2-69)



ACB Active carbon filter

STRUCTURE AND OPTIONS



60HZ Available in 60Hz version



3 YEARS WARRANTYPurchasing the replacement filter along with the vacuum



GRDGrounding



Stainless steel bin AISI 304



GX Stainless steel bin and chamber AISI 304



TX Stainless steel bin, chamber and frame AISI 304



100 LT 100 Lt bin



SPARK TRAP

Built to capture sparks produced during welding, sanding, or polishing operations on metal parts



ACCESSORIES



P12336

SUCTION ARM Ø 160MM/L 3M

160mm diameter suction arm jointed in three parts for a total length of 3 metres, equipped with an articulated hood and valve for adjusting ...



P12300/200

FLANGED REDUCTION FOR HOSE Ø 200MM

Coupling flange on DF industrial vacuum for 200 mm diameter flexible hose



P12300/180

FLANGED REDUCTION FOR HOSE Ø 180MM

Coupling flange on DF industrial vacuum for 180 mm diameter flexible hose



P12300/150

FLANGED REDUCTION FOR HOSE Ø 150MM

Coupling flange on DF industrial vacuum for 150 mm diameter flexible hose



P12300/120

FLANGED REDUCTION FOR HOSE Ø 120MM

Coupling flange on DF industrial vacuum for 120 mm diameter flexible hose



P12300/100

FLANGED REDUCTION FOR HOSE Ø 100MM

Coupling flange on DF industrial vacuum for 100 mm diameter flexible hose



P12334

FLANGED REDUCTION FOR ARM Ø 160MM

Coupling flange on DF industrial vacuum for 160 mm diameter flanged arm