

VACUUM CLEANERS FOR SCRAP, PACKAGING AND OEM

AS 550 TRIMMINGS AND PRODUCTION WASTE VACUUM CLEANER





FEATURES

- Suction of scraps and bulky cuttings
- Large collection capacity

- Can be installed directly on production lines
- Window to check fill level

HIGHLIGHTS



SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve to ensure continuous, maintenance-free work. A metal silencer is included as standard in the turbine to ensure a low noise level.



FILTERING COLLECTION BAG

Polyester bag filter for material collection that compacts material to the bottom, thus enabling the suction of large amounts of material



COLLECTION UNIT

The material is collected inside the large chamber of the coated steel vacuum cleaner.



LEVEL INSPECTION DOOR

An inspection window allows inspection of the amount of material inside the container without having to open the top cover

TECHNICAL DATA

MOTOR

Typologies	Side channel blower
Power	5,5 kW - 7,5 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	450 mBar
Maximum air flow	320 m3/h
Insulation class	55 F IP
Noise level	72 dB(A)

MACHINE


Suction inlet	70 Ø mm
Collection system	Steel container
Capacity	215 Lt
Dimensions	680 x 1200 mm
Height	1370 mm
Weight	115 Kg
Safety valve	Pressure relief valve

FILTRATION

Primary filter type	Bag
Media	Polyester



FEATURES



OPTIONS

Non-marking pivoting wheels

STRUCTURE AND OPTIONS



60HZ Available in 60Hz version



Rugged industrial coated steel construction

3 YEARS WARRANTY Purchasing the replacement filter along with the vacuum



Pressure relief valve installed

GRD Grounding

