

# **VACUUM CLEANERS FOR SCRAP, PACKAGING AND OEM**

# UPF 040 C INDUSTRIAL VACUUM FOR MACHINERY INSTALLATION





PUWER 0,4 kW - 0,5 HP



APPLICATION
Fine, dry and clogging powders



CAPACITY 10 Lt



### **FEATURES**

- Constant recovery of scraps or fine dust, production residues
- Available in horizontal and vertical construction
- Compact, for installation in narrow places
- Easy to maintain

# HIGHLIGHTS




#### **SUCTION UNIT**

The suction unit is a side channel blower with direct coupling between motor and impeller. The Side Channel Blower is equipped with a safety valve to ensure continuous, maintenance-free operation.



#### **FILTER UNIT**

Filtration is ensured by a Class M polyester cartridge filter (filtration efficiency 1 micron) with a high filtering surface area, which guarantees air passage even with a dirty filter.



#### INTERNAL DEFLECTOR

Sucked-in material is diverted by a deflector protecting the main filter.



#### **MODULARITY**

The vacuum cleaner, designed to be installed in narrow or hard-to-reach places, is available in vertical or horizontal versions so as to adapt to different needs.

## **TECHNICAL DATA**

MOTOR	
Typologies	Side channel blower
Power	0,4 kW - 0,5 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	125 mBar
Maximum air flow	80 m3/h
Insulation class	55   F IP
Noise level	64 dB(A)
·	

MACHINE	
Suction inlet	50 Ø mm
Collection system	AISI304 stainless steel container
Capacity	10 Lt
Dimensions	410 x 730 mm
Height	350 mm
Weight	42 Kg
Safety valve	Pressure relief valve

#### **FILTRATION**

Primary filter type	Cartridge
Filter surface	10000 cm2
EN 60335-2-69 filtration class	М
Media	Antistatic polyester



## **OPTIONS**

# **STRUCTURE AND OPTIONS**



**60HZ** 

Available in 60Hz version



#### **3 YEARS WARRANTY**

Purchasing the replacement filter along with the vacuum