

DUST COLLECTORS

DF 40 SP

INDUSTRIAL DUST COLLECTOR WITH INTEGRATED AUTOMATIC FILTER CLEANING



POWER
4 kW - 5,5 HP



APPLICATION
Volatile and suspended
powders



CAPACITY
65Lt

FEATURES

- Very high air flow for suspended dust
- Automatic filter cleaning system
- Sturdy painted steel construction
- Suction arm available (also Atex)

HIGHLIGHTS



TECHNICAL DATA

MOTOR

Typologies	Electric Fan
Power	4 kW - 5,5 HP
Frequency	50/60 Hz
Voltage	400 V
Maximum vacuum mmH2O	370 340 270 mmH2O
Static depression level	300 270 200 mmH2O
Maximum air flow	1500 2100 2700 m3/h
Insulation class	55 F IP
Noise level	73 dB(A)

MACHINE

Suction inlet	150 180 200 Ø mm
Collection system	Steel container
Capacity	65 Lt
Dimensions	630 x 1100 mm
Height	2500 mm
Weight	145 Kg

FILTRATION

Primary filter type	4x Cartridges
Filter surface	120000 cm2
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Filter Cleaning System	Automatic SP

FEATURES



PUSH HANDLE



PLUG
4-pole industrial plug



POWER SUPPLY CABLE



WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELS
Non-marking pivoting wheels



STEEL CONSTRUCTION
Rugged industrial coated steel construction

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 13
Absolute filter (EN 1822)
35.000 cm² filter surface
H13 Class Filter (EN 1822)
Glass fiber

STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



BX
Stainless steel bin AISI 304



GX
Stainless steel bin and chamber AISI 304



GRD
Grounding



SPARK TRAP
Built to capture sparks produced during welding, sanding, or polishing operations on metal parts

ACCESSORIES



P12300/150
FLANGED REDUCTION FOR HOSE Ø 150MM
Coupling flange on DF industrial vacuum for 150 mm diameter flexible hose



P12300/180
FLANGED REDUCTION FOR HOSE Ø 180MM
Coupling flange on DF industrial vacuum for 180 mm diameter flexible hose



P12300/200
FLANGED REDUCTION FOR HOSE Ø 200MM
Coupling flange on DF industrial vacuum for 200 mm diameter flexible hose



P12334
FLANGED REDUCTION FOR ARM Ø 160MM
Coupling flange on DF industrial vacuum for 160 mm diameter flanged arm



P12336
SUCTION ARM Ø 160MM/L 3M
160mm diameter suction arm jointed in three parts for a total length of 3 metres, equipped with an articulated hood and valve for adjusting ...