ATEX AND ACD VACUUM CLEANERS

FOX 5,5 DEX 1/3D

ATEX EXPLOSION-PROOF INDUSTRIAL VACUUM CLEANER

Watch the video!



POWER
4 kW - 5,5 HP

APPLICATION
Combustible dusts

CAPACITY
100 Lt

FEATURES

- Suitable and safe for intensive work in Atex 22 zones
- Certified Category 1D internal protection for maximum safety
- ATEX-certified blower
- High-efficiency antistatic filtration with integrated manual cleaning system

HIGHLIGHTS



SUCTION UNIT

The suction unit is a manufacturer-certified Atex side channel blower with direct coupling between motor and impeller. The Side Channel Blower is equipped with a safety valve that ensures continuous work, without any maintenance.



FILTER UNIT

The tangential inlet facilitates the cyclonic effect to deposit the collected material in the container. Filtration is ensured by a polyester star filter in class M (filtering efficiency 1 micron) with high filtering surface area, which guarantees air passage even with a dirty filter.



INTERNAL CERTIFICATION CAT 1D - ZONE 20

Thanks to its 1D – Zone 20 certified chamber, the vacuum cleaner guarantees maximum safety and compliance when vacuuming combustible or conductive dusts (Group IIIC), even when these are contained within the unit.



COLLECTION UNIT

The material is collected inside an AISI 304 stainless steel container, complete with a metal handle that allows its release, to avoid any sparks that could be generated by the electrostatic charge.

TECHNICAL DATA

MOTOR

Typologies	Atex 3D side channel blower
Power	4 kW - 5,5 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	230 mBar
Maximum air flow	450 m3/h
Insulation class	65 | F IP
Noise level	73 dB(A)

MACHINE

Atex marking	II 1/3D Ex htc IIIC T140°C Da/Dc
EX category	1/3D
Operating temperature	-20/+40 C°
Suction inlet	80 Ø mm
Collection system	AISI304 stainless steel container
Capacity	100 Lt
Dimensions	660 x 1200 mm
Height	1510 mm
Weight	157 Kg
Safety valve	Pressure relief valve

FILTRATION

Primary filter type	Star
Filter surface	24000 cm2
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Filter Cleaning System	Manual

FEATURES



THIRD PARTY ATEX CERTIFICATION



DRY TYPE VACUUM CLEANER
Atex-certified vacuum cleaner with dry dust filtration, as per EN17348



ANTISTATIC FILTRATION
Antistatic filtration to discharge static energy



4-PIN ATEX INDUSTRIAL PLUG



VACUUM GAUGE
Vacuum gauge for indication of filter clogged or in need of replacement



POWER SUPPLY CABLE




WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELS
Non-marking pivoting wheels



STEEL CONSTRUCTION
Rugged industrial coated steel construction




CYCLONIC EFFECT
Tangential inlet and cyclone installed



BX
Stainless steel bin AISI 304



PRV
Pressure relief valve installed



GRD
Grounding

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14
Absolute filter (EN 1822)
28.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber



PTFE ANT
Antistatlc PTFE filter (M class EN 60335-2-69)

STRUCTURE AND OPTIONS

60HZ

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



CONTAINER TILTABLE KIT
System for easy container emptying using forklift lifting.



SPARK TRAP
Built to capture sparks produced during welding, sanding, or polishing operations on metal parts



GX
Stainless steel bin and chamber AISI 304

ACCESSORIES



P12377
ANTISTATIC KIT PRO Ø 50MM
Electrically conductive solution for maximum protection against static discharge. - 3 m of electrically conductive EVA - 2 anti-static r ...



P13642
ANTISTATIC KIT PRO Ø 40MM
Complete antistatic system for thorough cleaning of sensitive production environments. - 3 m of electrically conductive EVA tubing - 1x ...



P12378
ANTISTATIC STARTER KIT Ø 50MM
Certified basic configuration for charge dissipation on medium-diameter cables. - 3 m of electrically conductive EVA - 2 anti-static rub ...



P13641
ANTISTATIC STARTER KIT Ø 40MM
Safety kit for areas with electrostatic hazards, ideal for fine and conductive dust. - 3 m of electrically conductive EVA tubing - 1x 50 ...



P14901/EX
VERTIDEX – ATEX-CERTIFIED ACCESSORY KIT FOR CLEANING AT HEIGHT Ø 40MM
An ultra-lightweight carbon fiber extension system, conductive and ATEX Category 2D certified, designed to reach hard-to-reach areas and ele ...