

ATEX AND ACD VACUUM CLEANERS

PUMA 30 S DEX 1/3D

ATEX EXPLOSION-PROOF INDUSTRIAL VACUUM CLEANER



POWER
18,5 kW - 25 HP



APPLICATION
Combustible dusts




CAPACITY
175 Lt

FEATURES


- Suitable and safe for intensive work in Atex 22 zones
- High efficiency antistatic filtration with integrated automatic cleaning system and grounding
- Maximum power thanks to the Atex certified turbine
- Ideal for large centralized suction systems

HIGHLIGHTS



SUCTION UNIT

The suction unit is a manufacturer-certified Atex side channel blower with direct coupling between motor and impeller. The Side Channel Blower is equipped with a safety valve that ensures continuous work, without any maintenance.



SP FILTER CLEANING SYSTEM

Automatic filter cleaning system in reverse flow of air at 6 bar (compressed air not supplied as standard). Each filter is cleaned at regular, alternately adjustable intervals without interrupting suction. Ideal for fine and difficult dust.



INTERNAL CERTIFICATION CAT 1D - ZONE 20

Thanks to its 1D - Zone 20 certified chamber, the vacuum cleaner guarantees maximum safety and compliance when vacuuming combustible or conductive dusts (Group IIIC), even when these are contained within the unit.



COLLECTION UNIT

The material is collected inside an AISI 304 stainless steel container, complete with a metal handle that allows its release, to avoid any sparks that could be generated by the electrostatic charge.

TECHNICAL DATA

MOTOR

Typologies	Atex 3D side channel blower
Power	18,5 kW - 25 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	380 mBar
Maximum air flow	1180 m3/h
Insulation class	65 F IP
Noise level	78 dB(A)

MACHINE

Atex marking	II 1/3D Ex htc IIIC T140°C Da/Dc
EX category	1/3D
Operating temperature	-10/+40 C°
Suction inlet	130 Ø mm
Collection system	AISI304 stainless steel container
Capacity	175 Lt
Dimensions	1050 x 1950 mm
Height	2300 mm
Weight	620 Kg
Safety valve	Pressure relief valve

FILTRATION

Primary filter type	4x Cartridges
Filter surface	180000 cm2
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Filter Cleaning System	Automatic SP

FEATURES



THIRD PARTY ATEX CERTIFICATION



DRY TYPE VACUUM CLEANER
Atex-certified vacuum cleaner with dry dust filtration, as per EN17348



ANTISTATIC FILTRATION
Antistatic filtration to discharge static energy



POWER SUPPLY CABLE



WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELS
Non-marking pivoting wheels



STEEL CONSTRUCTION
Rugged industrial coated steel construction



BX
Stainless steel bin AISI 304



5-PIN ATEX INDUSTRIAL PLUG



SP
Automatic reverse jet cleaning system



CYCLONIC EFFECT
Tangential inlet and cyclone installed



GRD
Grounding



FKL
Forklift bracket

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14

Absolute filter (EN 1822)
110.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber

STRUCTURE AND OPTIONS

60^{Hz}

60HZ

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with the vacuum



FLAMELESS VENT

A valve that contains the flame and the overpressure generated by a possible explosion.



PANEL VENT FOR DIRECTIONAL EXPLOSION

An explosion vent designed to break at a specific pressure and release the explosive pressure in a safe area.
Panel vent for explosion




GX

Stainless steel bin and chamber AISI 304



RC

Remote control 24V ON/OFF



CONTAINER TILTABLE KIT

System for easy container emptying using forklift lifting.

ACCESSORIES

**P14899****ANTISTATIC KIT Ø 70MM**

Maximum efficiency and antistatic safety for removing large volumes of conductive material. - 5-meter antistatic PUR hose - 2x antistati ...

**P09319****TILTABLE SEPARATOR WITH CYCLONE HEAD (580 LT)**

Separator in sturdy painted steel, can be lifted and tilted with the forklift. Fitted with a cyclone capable of breaking down the vacuumed m ...