

# ATEX AND ACD VACUUM CLEANERS

# FOX 5,5 DEX 1/2D ATEX EXPLOSION-PROOF INDUSTRIAL VACUUM CLEANER



Watch the video!











# **FEATURES**

- Suitable and safe for intensive work in Atex 21 zones
- ATEX-certified blower

- Category 1D certified internal protection for maximum safety
- High-efficiency antistatic filtration with integrated manual cleaning system

# HIGHLIGHTS



## **SUCTION UNIT**

The suction unit is a manufacturer-certified Atex side channel blower with direct coupling between motor and impeller. The Side Channel Blower is equipped with a safety valve that ensures continuous work, without any maintenance.



# **FILTER UNIT**

The tangential inlet facilitates the cyclonic effect to deposit the sucked material in the container. Filtration is provided by two progressive efficiency filters installed in series: a primary star polyester filter in class M (filtering efficiency 1 micron) with high filtering surface area and a secondary absolute filter in class H14.



# INTERNAL CERTIFICATION CAT 1D -

Thanks to its 1D - Zone 20 certified chamber, the vacuum cleaner guarantees maximum safety and compliance when vacuuming combustible or conductive dusts (Group IIIC), even when these are contained within the unit.



1/2D

# **COLLECTION UNIT**

The material is collected inside an AISI 304 stainless steel container, complete with a metal handle that allows its release, to avoid any sparks that could be generated by the electrostatic charge.

# **TECHNICAL DATA**

| MOTOR                    |                             |
|--------------------------|-----------------------------|
| Typologies               | Atex 3D side channel blower |
| Power                    | 4 kW - 5,5 HP               |
| Frequency                | 50/60 Hz                    |
| Voltage                  | 400 V                       |
| Vacuum in continuous run | 230 mBar                    |
| Maximum air flow         | 450 m3/h                    |
| Insulation class         | 65   F IP                   |
| Noise level              | 73 dB(A)                    |
|                          |                             |

## **MACHINE** II 1/2D Ex htc IIIC Atex marking T140°C Da/Dc **EX** category

| Operating temperature | -20/+40 C°                        |
|-----------------------|-----------------------------------|
| Suction inlet         | 80 Ø mm                           |
| Collection system     | AISI304 stainless steel container |
| Capacity              | 100 Lt                            |
| Dimensions            | 660 x 1200 mm                     |
| Height                | 1510 mm                           |
| Weight                | 157 Kg                            |
| Safety valve          | Pressure relief valve             |

### **FILTRATION**

| Primary filter type               | Star                 |
|-----------------------------------|----------------------|
| Filter surface                    | 24000 cm2            |
| EN 60335-2-69<br>filtration class | М                    |
| Media                             | Antistatic polyester |
| Filter Cleaning System            | Manual               |
| Secondary Absolute<br>Filter      | H14 - Included       |



# **FEATURES**



THIRD PARTY ATEX CERTIFICATION



DRY TYPE VACUUM CLEANER

Atex-certified vacuum cleaner with dry dust filtration, as per EN17348



**4-PIN ATEX INDUSTRIAL PLUG** 



ANTISTATIC FILTRATION

Antistatic filtration to discharge static energy



**VACUUM GAUGE** 

Vacuum gauge for indication of filter clogged or in need of replacement



**POWER SUPPLY CABLE** 



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



CYCLONIC EFFECT

Tangential inlet and cyclone installed



PRV

Pressure relief valve installed



GRD

Grounding



BX

Stainless steel bin AISI 304



HEPA 14

Absolute filter (EN 1822)



# **OPTIONS**

# **AVAILABLE FILTER MEDIA**



PTFE ANT Antistatlc PTFE filter (M class EN 60335-2-69)

# STRUCTURE AND OPTIONS

60<sup>®</sup> HZ

**60HZ** Available in 60Hz version



**3 YEARS WARRANTY**Purchasing the replacement filter along with the vacuum



**CONTAINER EMPTYING KIT**System for easy container emptying using forklift lifting.



**SPARK TRAP**Built to capture sparks produced during welding, sanding, or polishing operations on metal parts



**GX** Stainless steel bin and chamber AISI 304



# **ACCESSORIES**



### P13641

## ANTISTATIC STARTER KIT Ø 40MM

Basic kit containing antistatic accessories for application with 40 mm diameter ATEX vacuum cleaner



### P13642

# ANTISTATIC KIT PRO Ø 40MM

Kit containing antistatic accessories for application with 40 mm diameter ATEX vacuum cleaner



# P14901/EX

VERTIDEX — ATEX-CERTIFIED ACCESSORY KIT FOR CLEANING AT HEIGHT Ø 40MM



### P12378

### ANTISTATIC STARTER KIT Ø 50MM

Basic kit containing antistatic accessories for application with 50 mm diameter ATEX vacuum cleaner



## P12377

## ANTISTATIC KIT PRO Ø 50MM

Kit containing antistatic accessories for application with 50 mm diameter ATEX vacuum cleaner