ATEX AND ACD VACUUM CLEANERS

PUMA 15 DEX 1/2D

EXPLOSION-PROOF ATEX INDUSTRIAL VACUUM CLEANER

POWER
11 kW - 15 HP

APPLICATION
Combustible dusts

CAPACITY
175 Lt

FEATURES

- Suitable and safe for intensive work in Atex 21 or 22 zones
- Maximum safety thanks to antistatic filtration and complete earthing
- Maximum power thanks to the Atex certified blower
- Ideal for large centralized suction systems

HIGHLIGHTS

SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve to ensure continuous, maintenance-free work. A metal silencer is included as standard in the turbine to ensure a low noise level.

FILTER UNIT

The tangential inlet facilitates the cyclonic effect to deposit the sucked material in the container. Filtration is provided by two progressive efficiency filters installed in series: a primary star polyester filter in class M (filtering efficiency 1 micron) with high filtering surface area and a secondary absolute filter in class H14.

INTERNAL CERTIFICATION CAT 1D - ZONE 20

Thanks to its 1D – Zone 20 certified chamber, the vacuum cleaner guarantees maximum safety and compliance when vacuuming combustible or conductive dusts (Group IIIC), even when these are contained within the unit.

COLLECTION UNIT

The material is collected inside an AISI 304 stainless steel container, complete with a metal handle that allows its release, to avoid any sparks that could be generated by the electrostatic charge.

TECHNICAL DATA

MOTOR

Typologies	Atex 3D side channel blower
Power	11 kW - 15 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	300 mBar
Maximum air flow	920 m3/h
Insulation class	65 | F IP
Noise level	74 dB(A)

MACHINE

Atex marking	II 1/2D Ex htc IIIC T140°C Da/Dc
EX category	1/2D
Operating temperature	-10/+40 C°
Suction inlet	100 Ø mm
Collection system	AISI304 stainless steel container
Capacity	175 Lt
Dimensions	850 x 1550 mm
Height	1980 mm
Weight	270 Kg
Safety valve	Pressure relief valve

FILTRATION

Primary filter type	Star
Filter surface	45000 cm2
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Filter Cleaning System	Manual
Secondary Absolute Filter	H14 - Included

FEATURES

THIRD PARTY ATEX CERTIFICATION

DRY TYPE VACUUM CLEANER

Atex-certified vacuum cleaner with dry dust filtration, as per EN17348

HEPA 14

Absolute filter (EN 1822)

ELECTRICAL PANEL

Electrical panel, implementable with additional functions

4-PIN ATEX INDUSTRIAL PLUG

ANTISTATIC FILTRATION

Antistatic filtration to discharge static energy

VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement

POWER SUPPLY CABLE

WHEEL WITH BRAKE

Non-marking wheel with integrated brake

WHEELS

Non-marking pivoting wheels

STEEL CONSTRUCTION

Rugged industrial coated steel construction



CYCLONIC EFFECT

Tangential inlet and cyclone installed

PRV

Pressure relief valve installed

GRD

Grounding

BX

Stainless steel bin AISI 304

OPTIONS

AVAILABLE FILTER CLEANING SYSTEMS

SP

Automatic reverse jet cleaning system
Antistatic M class filter (EN 60335-2-69), 4 Polyester filter cartridges, 12 m² filter surface

AVAILABLE FILTER MEDIA

PTFE ANT

Antistatlc PTFE filter (M class EN 60335-2-69)

STRUCTURE AND OPTIONS

60HZ
Available in 60Hz version

3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum

CONTAINER TILTABLE KIT
System for easy container emptying using forklift lifting.

FLAMELESS VENT
A valve that contains the flame and the overpressure generated by a possible explosion.

PANEL VENT FOR DIRECTIONAL EXPLOSION
An explosion vent designed to break at a specific pressure and release the explosive pressure in a safe area.
Panel vent for explosion

FKL
Forklift bracket

GX
Stainless steel bin and chamber AISI 304

ACCESSORIES

P14899
ANTISTATIC KIT Ø 70MM
Maximum efficiency and antistatic safety for removing large volumes of conductive material. - 5-meter antistatic PUR hose - 2x antistati ...