

ATEX AND ACD VACUUM CLEANERS

PUMA 30 S 1/2D Z20/21

ATEX EXPLOSION-PROOF INDUSTRIAL VACUUM CLEANER



POWER
18,5 kW - 25 HP



APPLICATION
Combustible dusts

FEATURES

- Suitable and safe for intensive work in Atex 21 zones
- High efficiency antistatic filtration with integrated automatic cleaning system and grounding
- Maximum power thanks to the Atex certified blower
- Ideal for large centralized suction systems

HIGHLIGHTS




SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve to ensure continuous, maintenance-free work. A metal silencer is included as standard in the turbine to ensure a low noise level.



FILTER UNIT

The tangential inlet facilitates the cyclonic effect to deposit the collected material in the container. Filtration is ensured by a polyester star filter in class M (filtering efficiency 1 micron) with high filtering surface area, which guarantees air passage even with a dirty filter.



SP FILTER CLEANING SYSTEM

Automatic filter cleaning system in reverse flow of air at 6 bar (compressed air not supplied as standard). Each filter is cleaned at regular, alternately adjustable intervals without interrupting suction. Ideal for fine and difficult dust.



COLLECTION UNIT

The material is collected inside an AISI 304 stainless steel container, complete with a metal handle that allows its release, to avoid any sparks that could be generated by the electrostatic charge.

TECHNICAL DATA

MOTOR

Typologies	Atex side channel blower
Power	18,5 kW - 25 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	380 mBar
Maximum air flow	1180 m3/h
Insulation class	65 F IP
Noise level	78 dB(A)

MACHINE

Atex marking	II 1/2D Ex htc IIIC T140°C Da/Dc
EX category	1/2D
Operating temperature	-10/+40 C°
Suction inlet	130 Ø mm
Dimensions	1050 x 1950 mm
Height	2300 mm
Weight	620 Kg
Safety valve	Pressure relief valve

FILTRATION

Primary filter type	4x Cartridges
Filter surface	180000 cm2
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Filter Cleaning System	Automatic SP
Secondary Absolute Filter	H14 - Included

FEATURES



THIRD PARTY ATEX CERTIFICATION



4-PIN ATEX INDUSTRIAL PLUG



ANTISTATIC FILTRATION

Antistatic filtration to discharge static energy



POWER SUPPLY CABLE



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction




BX

Stainless steel bin AISI 304



SP

Automatic reverse jet cleaning system



CYCLONIC EFFECT

Tangential inlet and cyclone installed



GRD

Grounding



FKL

Forklift bracket

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14

Absolute filter (EN 1822)
110.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber

STRUCTURE AND OPTIONS

60^{Hz}

60HZ

Available in 60Hz version



3 YEARS WARRANTY

Purchasing the replacement filter along with the vacuum



FLAMELESS VENT

A valve that contains the flame and the overpressure generated by a possible explosion.



PANEL VENT FOR DIRECTIONAL EXPLOSION

An explosion vent designed to break at a specific pressure and release the explosive pressure in a safe area.
Panel vent for explosion




GX

Stainless steel bin and chamber AISI 304



RC

Remote control 24V ON/OFF



CONTAINER EMPTYING KIT

System for easy container emptying using forklift lifting.

ACCESSORIES



P09319

TILTABLE SEPARATOR WITH CYCLONE HEAD (580 LT)

Separator in sturdy painted steel, can be lifted and tilted with the forklift. Fitted with a cyclone capable of breaking down the vacuumed m ...