

ATEX AND ACD VACUUM CLEANERS

AC 100 3GD Z2-22

ATEX PNEUMATIC INDUSTRIAL VACUUM CLEANER



APPLICATION
Powders, solids and shavings



CAPACITY
100 Lt

FEATURES

- Suitable and safe for intensive work in Atex zones 2 or 22
- High filtration capacity and efficiency
- Powered by compressed air
- Multiple construction options available

HIGHLIGHTS




SUCTION UNIT

Suction is generated by a venturi tube, a device that makes it possible to generate excellent suction performance without any kind of mechanical movement or electrical component.



FILTER UNIT

The tangential inlet facilitates the cyclonic effect to deposit the collected material in the container. Filtration is ensured by a polyester star filter in class M (filtering efficiency 1 micron) with high filtering surface area, which guarantees air passage even with a dirty filter.



FILTER CLEANING SYSTEM

An ergonomic manual filter shaker allows the filter to be cleaned easily and quickly, removing dust and debris from the surface of the filter.



COLLECTION UNIT

The material is collected inside an AISI 304 stainless steel container, complete with a metal handle that allows its release, to avoid any sparks that could be generated by the electrostatic charge.

TECHNICAL DATA

MOTOR

Typologies	Venturi tube
Vacuum in continuous run	500 mBar
Maximum air flow	480 m ³ /h
Noise level	70 dB(A)
Air required	1233 lt/min
Pressure requirement	6 - 8 Bar

MACHINE

Atex marking	II 3GD Ex htc IIIB T100°C Gc/Dc
EX category	3GD
Operating temperature	-10/+40 °C
Suction inlet	80 Ø mm
Collection system	AISI304 stainless steel container
Capacity	100 Lt
Dimensions	660 x 800 mm
Height	1200 mm
Weight	66 Kg

FILTRATION

Primary filter type	Star
Filter surface	24000 cm ²
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Filter Cleaning System	Manual

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14
Absolute filter (EN 1822)
22.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber



PTFE ANT
Antistatic PTFE filter (M class EN
60335-2-69)

STRUCTURE AND OPTIONS



3 YEARS WARRANTY
Purchasing the replacement filter along with
the vacuum



GX
Stainless steel bin and chamber AISI 304

ACCESSORIES



P12377
ANTISTATIC KIT PRO Ø 50MM
Kit containing antistatic accessories for
application with 50 mm diameter ATEX
vacuum cleaner



P13642
ANTISTATIC KIT PRO Ø 40MM
Kit containing antistatic accessories for
application with 40 mm diameter ATEX
vacuum cleaner



P12378
ANTISTATIC STARTER KIT Ø 50MM
Basic kit containing antistatic accessories for
application with 50 mm diameter ATEX
vacuum cleaner



P13641
ANTISTATIC STARTER KIT Ø 40MM
Basic kit containing antistatic accessories for
application with 40 mm diameter ATEX
vacuum cleaner