

ATEX AND ACD VACUUM CLEANERS

M 45 H ACD INERT

INDUSTRIAL VACUUM FOR INERTIZING COMBUSTIBLE DUSTS



POWER
2,6 kW - 3,5 HP



APPLICATION
Combustible dusts



COLLECTION SYSTEM
Container with inertizing
bath

FEATURES

- Classified ACD for suction of combustible dust in non-Atex zones
- Ideal for safely extracting conductive metallic dusts
- Container with an inert liquid bath that prevents the formation of explosive atmospheres inside the vacuum
- Vacuum gauge to monitor performance

HIGHLIGHTS



SUCTION UNIT

Suction is provided by 2 by-pass motors controlled by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



FILTER UNIT

Filtration is provided by two progressive efficiency filters installed in series: a primary star polyester filter class M (filtering efficiency 1 micron) with high filtering surface area and an absolute secondary filter in class H14.



DESIGNED FOR COMBUSTIBLE DUST

Ideal for collecting fine and potentially combustible dust in non-ATEX classified areas. The ACD vacuum is equipped with antistatic filters and full grounding to ensure safe and reliable operation.



INERTING LIQUID BATH

Container with conductive dust immersion system. Prevents the formation of explosive atmospheres inside the vacuum cleaner by neutralizing incoming dust.

TECHNICAL DATA

MOTOR


Typologies	By-pass
Power	2,6 kW - 3,5 HP
Frequency	50/60 Hz
Voltage	230 V
Vacuum in continuous run	250 mBar
Maximum air flow	380 m3/h
Insulation class	54 F IP
Noise level	72 dB(A)

MACHINE

Suction inlet	50 Ø mm
Collection system	AISI304 stainless steel container
Capacity	45 Lt
Liquid discharge system	Discharge valve
Dimensions	550 x 620 mm
Height	1400 mm
Weight	50 Kg
Solid separation	Basket grid
Liquid separation	PPL bag 150µm
Safety valve	2x Hydrogen Vent

FILTRATION

Primary filter type	Cartridge
Filter surface	35000 cm2
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Additional filter	Spark trap
Secondary Absolute Filter	H14 - Included

FEATURES

ANTI-SPARK FILTER

Protective filter that prevents the passage of sparks


HYDROGEN VENT

Safety valve to let out any gases formed inside the aspirator


PUSH HANDLE

SHUKO TYPE PLUG

POWER SUPPLY CABLE

WHEEL WITH BRAKE

Non-marking wheel with integrated brake


WHEELS

Non-marking pivoting wheels


STEEL CONSTRUCTION

Rugged industrial coated steel construction


BX

Stainless steel bin AISI 304


FILTER CLOGGING INDICATOR

Filter clogged or need to be replaced indicator light


GRD

Grounding


HEPA 14

Absolute filter (EN 1822)

OPTIONS

STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum

ACCESSORIES



P12377
ANTISTATIC KIT PRO Ø 50MM
Kit containing antistatic accessories for application with 50 mm diameter ATEX vacuum cleaner



P12378
ANTISTATIC STARTER KIT Ø 50MM
Basic kit containing antistatic accessories for application with 50 mm diameter ATEX vacuum cleaner