ATEX AND ACD VACUUM CLEANERS

CVS 200 3D Z22

ATEX CERTIFIED SUCTION UNIT FOR CENTRALIZED SYSTEMS




POWER
22 kW - 30 HP

APPLICATION
Powders, solids and shavings

FEATURES

- Powerful Atex-certified side-channel blowers suitable for continuous operation
- Reliable suction unit for centralized suction systems Atex
- Easy to move with a forklift
- Multiple construction options available

HIGHLIGHTS



SUCTION UNIT

The suction unit is a manufacturer-certified Atex side channel blower with direct coupling between motor and impeller. The Side Channel Blower is equipped with a safety valve that ensures continuous work, without any maintenance.




EASY HANDLING

Two pass-through guides located on the bottom facilitate handling of the unit by forklift truck



ELECTRICAL PANEL WITH REMOTE START

Management via electrical panel equipped with star/delta start and remote control. Implementable with additional functions



REQUIRES FILTRATION UNIT

This unit does not include filtration and collection units, it requires coupling with a filter pre-separator or similar unit

TECHNICAL DATA

MOTOR

Typologies	Atex side channel blower
Power	22 kW - 30 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	200 mBar
Maximum air flow	1985 m3/h
Insulation class	55 | F IP
Noise level	74 dB(A)
Remote control	Free connector available
Electrical panel	Included

MACHINE

Atex marking	II 3D Ex htc IIIB T140°C Dc
EX category	3D
Operating temperature	-10/+40 C°
Suction inlet	127 Ø mm
Dimensions	821 x 1319 mm
Height	1792 mm
Weight	290 Kg
Safety valve	Pressure relief valve
Forklift support	Included

FEATURES

ATEX CERTIFICATION



ELECTRICAL PANEL
Electrical panel, implementable with additional functions



PLUG
4-pole industrial plug



VACUUM GAUGE
Vacuum gauge for indication of filter clogged or in need of replacement



POWER SUPPLY CABLE



STEEL CONSTRUCTION
Rugged industrial coated steel construction



PRV
Pressure relief valve installed

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14
Absolute filter (EN 1822)
110.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber


STRUCTURE AND OPTIONS



60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



NON-RETURN VALVE
Isolates explosion and prevents it from spreading from the industrial vacuum to the pipe