

SINGLE-PHASE WET&DRY INDUSTRIAL VACUUM CLEANERS

XM 35 FP

INDUSTRIAL VACUUM FOR SURFACE PREPARATION



POWER
2,6 - 3,5



APPLICATION
Toxic or hazardous dusts



COLLECTION SYSTEM
Endless bag

FEATURES


- Designed for fine dust in surface preparation applications
- Telescopic frame for easy transportation
- Automatic integrated filter cleaning
- Large container for collecting the vacuumed material

HIGHLIGHTS



SUCTION UNIT

Suction is provided by 2 by-pass motors controlled by independent switches, allowing the operator to control suction performance. The motors are located inside a robust enclosure, with an insulating sponge to maintain a low noise level.



FILTER UNIT

Filtration is ensured by a class M polyester cartridge filter (filtration efficiency 1 micron) with a high filter surface area, which guarantees air passage even with a dirty filter. A vibration cleaning system keeps the filter efficient even during long work sessions.



POWER TOOL SOCKET

A 24VAC outlet allows hand-held power tools to be connected and the remote switching on and off of the vacuum cleaner to be subordinated.



COLLECTION UNIT

The material is collected inside a coated bin complete with a handle that allows it to be released. Thanks to the 4 sturdy pivoting wheels, the container can be moved with ease and the collected material can then be disposed of.

TECHNICAL DATA

MOTOR

Typologies	By-pass
Power	2,6 - 3,5
Frequency	50 Hz
Voltage	230 V
Maximum vacuum mmH2O	250 mmH2O
Maximum air flow	380 m3/h
Noise level	72 dB(A)
Remote control	Power tool socket

MACHINE

Suction inlet	50 Ø mm
Collection system	Steel container
Capacity	45 Lt
Dimensions	585 x 545 mm
Height	1395 mm
Weight	45 Kg

FILTRATION

Primary filter type	Cartridge
Filter surface	35000 cm2
EN 60335-2-69 filtration class	M
Media	PTFE coated polyester
Filter Cleaning System	Vibro

FEATURES



RC SCHUKO
Remote control by power tool (MAX 2000 W)



FILTER CLOGGING INDICATOR
Filter clogged or need to be replaced
indicator light



POWER SUPPLY CABLE



SHUKO TYPE PLUG



PUSH HANDLE



WHEEL WITH BRAKE
Non-marking wheel with integrated brake



WHEELS
Non-marking pivoting wheels



STEEL CONSTRUCTION
Rugged industrial coated steel construction

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 13
Absolute filter (EN 1822)
35.000 cm² filter surface
H13 Class Filter (EN 1822)
Glass fiber


STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



AB
Accessories basket



GRD
Grounding

ACCESSORIES



P13638
STARTER KIT Ø 40MM
Basic kit containing specific accessories for 40 mm diameter solids and liquids vacuuming



P12350
STARTER KIT Ø 50MM
Basic kit containing specific accessories for 50 mm diameter solids and liquids vacuuming



P13640
DRY KIT Ø 40MM
Kit containing specific accessories for 40 mm diameter dust and solids vacuuming



P12348
DRY KIT Ø 50MM
Kit containing specific accessories for 50 mm diameter dust and solids vacuuming