

ACCESSORIES

HOPPER PRE-SEPARATOR HOPPER PRE-SEPARATOR FOR BIG-BAG DISCHARGE





APPLICATION

Fine, dry and clogging powders



COLLECTION SYSTEMLocalized discharge




FEATURES

- Collection and direct unloading into Big-Bags
- Modular and customizable solution

• Safe and effective disposal

HIGHLIGHTS





CUSTOM EXHAUST SYSTEM


A specific discharge system, intermittent or continuous, can be installed depending on operational needs.


TECHNICAL DATA

MACHINE

Intake suction inlet	70
Outlet suction inlet	100 Ø mm
Collection system	Conveyed discharge
Capacity	200 Lt
Dimensions	1500 x 1500 mm
Height	2760 mm
Forklift support	Included

FEATURES







OPTIONS

STRUCTURE AND OPTIONS



DISCHARGE WITH COUNTERBALANCED

The material is automatically discharged every time suction is stopped.



DISCHARGE WITH BUTTERFLY VALVE

Manual intermittent discharging system with butterfly valve Manual discharging butterfly valve



DOUBLE PNEUMATIC DISCHARGE WITH **BUTTERFLY VALVES**

System with valves that open alternately to allow the material to be discharged and the vacuum to be maintained at the same time. Double electro pneumatic discharging butterfly valve ATEX



DOUBLE DISCHARGE WITH ELECTRO-PNEUMATIC DAMPERS

System with dampers that open alternately to allow the material to be discharged and the vacuum to be maintained at the same time.



ROTARY VALVE FOR CONTINUOUS DISCHARGE

The valve rotates continuously allowing a constant and uniform discharge of the aspirated material.
Rotary valve for continuous hopper discharge



ROTARY LEVEL SENSOR

Sensor with rotating paddle that sends a signal when the container is full to immediately stop suction