

HEAVY DUTY THREE-PHASE INDUSTRIAL VACUUM CLEANERS

PUMA 15 S

HIGH-POWER INDUSTRIAL VACUUM FOR COMBUSTIBLE DUST



POWER
11 kW - 15 HP



APPLICATION
Combustible dusts



CAPACITY
175 Lt

FEATURES

- ACD classified for combustible dust extraction in non-Atex classified areas
- Multiple construction options available
- Can also be used in heavy-duty and continuous applications
- Can be integrated into centralized vacuum systems

HIGHLIGHTS



SUCTION UNIT

The suction unit is a side channel blower with direct coupling between motor and impeller. The turbine is equipped with a safety valve to ensure continuous, maintenance-free work. A metal silencer is included as standard in the turbine to ensure a low noise level.



FILTER UNIT

The tangential inlet facilitates the cyclonic effect to deposit the collected material in the container. Filtration is ensured by a polyester star filter in class M (filtering efficiency 1 micron) with high filtering surface area, which guarantees air passage even with a dirty filter.



DESIGNED FOR COMBUSTIBLE DUST

Ideal for collecting fine and potentially combustible dust in non-ATEX classified areas. The ACD vacuum is equipped with antistatic filters and full grounding to ensure safe and reliable operation.



COLLECTION UNIT

The material is collected inside a coated bin complete with a handle that allows it to be released. Thanks to the 4 sturdy pivoting wheels, the bin can be moved with ease and the collected material can then be disposed of.

TECHNICAL DATA

MOTOR

Typologies	Side channel blower
Power	11 kW - 15 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	440 mBar
Maximum air flow	550 m3/h
Insulation class	55 F IP
Noise level	74 dB(A)
Remote control	Free connector available

MACHINE

Suction inlet	100 Ø mm
Collection system	Steel container
Capacity	175 Lt
Dimensions	850 x 1550 mm
Height	1980 mm
Weight	310 Kg
Safety valve	Pressure relief valve
Forklift support	Included

FILTRATION

Primary filter type	Star
Filter surface	45000 cm2
EN 60335-2-69 filtration class	M
Media	Polyester
Filter Cleaning System	Manual

FEATURES



VACUUM GAUGE

Vacuum gauge for indication of filter clogged or in need of replacement



POWER SUPPLY CABLE



PLUG

4-pole industrial plug



WHEEL WITH BRAKE

Non-marking wheel with integrated brake



WHEELS

Non-marking pivoting wheels



STEEL CONSTRUCTION

Rugged industrial coated steel construction



ANTISTATIC FILTRATION

Antistatic filtration to discharge static energy



CYCLONIC EFFECT

Tangential inlet and cyclone installed



PRV

Pressure relief valve installed



ELECTRICAL PANEL

Electrical panel, implementable with additional functions



GRD

Grounding

OPTIONS
AVAILABLE FILTER CLEANING SYSTEMS

SP

Automatic reverse jet cleaning system
 Antistatic M class filter (EN 60335-2-69), 4
 Polyester filter cartridges, 12 m² filter surface


SE

Semiautomatic electrical filter shaker


PSC

Semiautomatic pneumatic filter shaker


COM

Compressor on board
 Compressor fitted on the back cover

AVAILABLE FILTER MEDIA

HEPA 14

Absolute filter (EN 1822)
 110.000 cm² filter surface
 H14 Class Filter (EN 1822)
 Glass fiber

STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



ATEX CERTIFICATION



CONTAINER EMPTYING KIT
System for easy container emptying using forklift lifting.



GFR
Lifting eyebolts



FKL
Forklift bracket



BX
Stainless steel bin AISI 304



GX
Stainless steel bin and chamber AISI 304

ACCESSORIES



P14899
ANTISTATIC KIT Ø 70MM
Complete kit of antistatic accessories for vacuuming dust and solids with a diameter of 70 mm.