

ATEX AND ACD VACUUM CLEANERS

TX 400 S ACD

MOBILE INDUSTRIAL VACUUM FOR COMBUSTIBLE DUST



POWER
4 kW - 5,5 HP



APPLICATION
Combustible dusts






CAPACITY
100 Lt

FEATURES

- ACD classified for combustible dust extraction in non-Atex classified areas
- High filtration efficiency in class M
- Compact structure for maximum stability and maneuverability
- Vacuum gauge for performance monitoring

HIGHLIGHTS



TECHNICAL DATA

MOTOR

Typologies	Side channel blower
Power	4 kW - 5,5 HP
Frequency	50/60 Hz
Voltage	400 V
Vacuum in continuous run	360 mBar
Maximum air flow	330 m3/h
Insulation class	55 F IP
Noise level	76 dB(A)

MACHINE

Suction inlet	70 Ø mm
Collection system	Steel container
Capacity	100 Lt
Dimensions	650 X 1100 mm
Height	1400 mm
Weight	140 Kg
Safety valve	Pressure relief valve

FILTRATION

Primary filter type	Star
Filter surface	38000 cm2
EN 60335-2-69 filtration class	M
Media	Antistatic polyester
Filter Cleaning System	Manual

OPTIONS

AVAILABLE FILTER MEDIA



HEPA 14
Absolute filter (EN 1822)
28.000 cm² filter surface
H14 Class Filter (EN 1822)
Glass fiber



PTFE ANT
Antistatic PTFE filter (M class EN
60335-2-69)

AVAILABLE FILTER CLEANING SYSTEMS



SP
Automatic reverse jet cleaning system
Antistatic M class filter (EN 60335-2-69), 3
Polyester filter cartridges, 9 m² filter surface



PSC
Semiautomatic pneumatic filter shaker


STRUCTURE AND OPTIONS

60^{Hz}

60HZ
Available in 60Hz version



3 YEARS WARRANTY
Purchasing the replacement filter along with the vacuum



CYCLONIC EFFECT
Tangential inlet and cyclone installed
Tangential inlet + cyclone



BX
Stainless steel bin AISI 304



GX
Stainless steel bin and chamber AISI 304



SPARK TRAP
Built to capture sparks produced during welding, sanding, or polishing operations on metal parts

ACCESSORIES



P13641
ANTISTATIC STARTER KIT Ø 40MM
Safety kit for areas with electrostatic hazards, ideal for fine and conductive dust. - 3 m of electrically conductive EVA tubing - 1x 50 ...



P13642
ANTISTATIC KIT PRO Ø 40MM
Complete antistatic system for thorough cleaning of sensitive production environments. - 3 m of electrically conductive EVA tubing - 1x ...



P12377
ANTISTATIC KIT PRO Ø 50MM
Electrically conductive solution for maximum protection against static discharge. - 3 m of electrically conductive EVA - 2 anti-static r ...



P12378
ANTISTATIC STARTER KIT Ø 50MM
Certified basic configuration for charge dissipation on medium-diameter cables. - 3 m of electrically conductive EVA - 2 anti-static rub ...



P14900
VERTIVAC – CONDUCTIVE ACCESSORY KIT FOR CLEANING AT HEIGHT Ø 40MM
An ultra-lightweight, conductive carbon fiber extension system designed to safely reach hard-to-reach spots and elevated structures from the ...